



Speed & Area Meters

A versatile range of instruments to measure and monitor numerous machine functions simultaneously



The **RDS SAM** range of speed and area measurement instruments is an easy to use and cost-effective method of collecting fieldwork data for cost analysis relevant to both farmers and contractors.

RDS offers three different SAM variants for measuring and monitoring various machine functions for accurate fieldwork.

Each SAM instrument displays the selected channel, chosen by scrolling with the central button. Information can be in metric or imperial units and is easily switched between the two at any time. The SAM instrument can be programmed by the operator for implements of any practical width and for any wheel size.

Each SAM unit offers various functions as shown opposite. An automatic cut-out switch to prevent area accumulation when turning on headlands etc comes as standard on each model. The SAM 400 also offers two programmable forward speed alarm outputs that can be used to control various aspects of machine operation e.g engine cut-off.

A 'transfer kit' is available if a unit is to be used on a number of vehicles; this enables the head unit to be transferred easily between vehicles.



Monitor functions:

	SAM 100	SAM 200	SAM 400
Forward speed channel (mph or kmph):	✓	✓	✓
Partial Area channel (Ha/acres):		✓	✓
Total Area channel (Ha/acres):	✓	✓	✓
Work rate(Ha/hr or acres/hr):		✓	✓
Engine hours:		✓	✓
RPM (optional):		✓	✓
Partial/Total distance (miles/kms):			✓
Automatic cut-out switch:	✓	✓	✓
2 Programmable forward speed alarms:			✓
Optional Width Compensation Interface:	✓		✓
Optional Area Compensation Interface:	✓	✓	✓
Optional vehicle transfer kit:	✓	✓	✓
Optional shaft speed sensor:		✓	✓

Technical data:

- Voltage: 10 - 30 Vdc
- Temperature: -20 to +40°C operation
-30 to +70°C storage
- Display: 4-digit, illuminated LCD
- Protection: IP67
- Shaft speeds: 0 to 9999 RPM

Warranty: 2 years

System extensions:

RDS ACI - an area compensation interface for accurate area monitoring when connected to a machine's switchbox.

RDS WCI - a width compensation interface for accurate area monitoring when using partial implement width.

Forward speed - radar or GPS signal inputs can be used to give forward speed readings. An interface is required to convert GPS signal into a radar pulse for the instrument.

Available from:

Also in the range:

Errors and omissions excepted, technical details are subject to change.ref:SAM/EN/AHK rev 1.0